

300 PSI rated pressure



A53

GATE VALVE

FEMALE x MALE hose connection


Polished Brass



Rough Chrome



Polished Chrome



SIZE (a x b)	CERTIFICATIONS	A	B	C	D	E
2 1/2" x 2 1/2"	 FM APPROVED UL LISTED LISTED 618R	5 1/8"	9 13/16"	2 1/4"	2 1/16"	4 11/32"
3" x 2 1/2"	 FM APPROVED	5 1/8"	9 15/16"	2 1/4"	2 3/16"	4 17/32"

Straightway pattern, non-rising stem, 300 lbs. hose gate valves are intended for use on standpipes, fire pumps and hydrants.

Standard equipment:

Female NPT inlet x male hose thread outlet, forged brass with red handwheel, solid wedge disc with tapered seats.
Available without cap and chain.

RELATED PRODUCTS

A97 p. 16



A98 p. 17



A111 p. 22

300 PSI rated pressure



A53G

SINGLE HYDRANT GATE VALVE


MALE x FEMALE SWIVEL



NOTE: Particularly recommended when space limitation precludes a permanent type installation.



OPTIONAL TRIM:
Swivel inlet with rocker lugs.



SIZE (a x b)	CERTIFICATIONS	A	B	C	D	E
2 1/2" x 2 1/2"	 LISTED 618R	5 1/8"	9 13/16"	2 1/4"	2 1/16"	5 5/16"

Straightway pattern, non-rising stem, 300 lbs. hose gate valves are intended for use on standpipes, fire pumps and hydrants.

Standard equipment:

Brass body with brass trim, pin lug, male inlet x female hose thread swivel.
Red handwheel.

RELATED PRODUCTS

A81 p. 35



A97 p. 16



A98 p. 17