



PINOLEAKPES
NO LEAK BETWEEN THE PIPES

FIRE PROTECTION SOLUTIONS

MECH[®]

GEAR OPERATED BUTTERFLY VALVE WITH SUPERVISORY SWITCH



GEAR
OPERATED



SUPERVISORY
SWITCH



RELIABLE
PERFORMANCE



FIRE PROTECTION
APPROVED



LISTED




APPROVED

The MECH Gear Operated Butterfly Valve with Supervisory Switch is designed for fire protection systems, providing reliable on-off and throttling service. Its robust construction and high-quality materials ensure long service life and dependable performance in demanding applications.

FEATURES

- Gear operated for smooth and easy operation
- Supervisory switch for valve position monitoring
- Wafer design for easy installation between flanges
- Ductile iron body and disc for high strength and durability
- NBR seat for excellent sealing performance
- UL Listed and FM Approved for fire protection applications
- Suitable for on-off and throttling service

DIMENSIONS (mm)



SIZE	A	B	C	D	E	F	G	H
12"	300	530	280	190	78	45	24	Ø12

Dimensions are for reference only and subject to change without notice.



SPECIFICATIONS

Size	12" (300mm)
Model	XD371X
Body Material	Ductile Iron ASTM A536
Disc	Ductile Iron
Seat	NBR
Connection	Wafer Type
Max. Working Pressure	300 PSI (20.7 Bar)
Approvals	UL / FM
Operation	Gear Operated
Supervisory Switch	Yes
Color	Red
Application	Fire Protection Systems
Temperature Range	-10°C to 80°C

MATERIALS OF CONSTRUCTION

PART	MATERIAL
Body	Ductile Iron ASTM A536
Disc	Ductile Iron
Seat	NBR
Shaft	Stainless Steel
O-Ring	NBR
Gear Box	Ductile Iron
Handwheel	Ductile Iron
Switch	Supervisory Switch



(02) 8 362 8888



sales@pinoleakpes.com



www.pinoleakpes.com

**QUALITY PRODUCTS.
TRUSTED SOLUTIONS.**

DISTRIBUTED BY: