

LL1581 | Ball valve, with pipe connection, T handle



CE EAC

Features		
Working pressure 16 bar (232 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	16-2.0	20-2.0

LL1582 | Ball valve, with pipe connection, T handle



CE EAC

Features		
Working pressure 16 bar (232 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2"x16-2.0	3/4"x20-2.0

LL1031 | Ball valve, with pipe connection, flat lever handle



CE EAC

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	15	22 28

LL1043 | Ball valve, with pipe connection, T handle



CE ACS EAC

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	15	22 28



LL1583 | Ball valve, with pipe connection, T handle



CE EAC

Features		
Working pressure 16 bar (232 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2"x16-2.0	3/4"x20-2.0

LL1804 | Quick insert ball valve



CE

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	20	25



LL1019 | Ball valve, full flow, female/female flat lever handle



Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/4" 3/8" 1/2" 3/4" 1" 1 1/4" 1 1/2" 2" 2 1/2" 3" 4"	

LL1091 | Ball valve, C/C flat lever handle



Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2" 3/4" 1" 1 1/4" 1 1/2" 2"	15.93 22.28 28.65 35 41.35 54.05

LL1101 | Built-in ball valve, full flow, female/female



CE ACS EAC

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2"	3/4"

LL1100 | Built-in ball valve, full flow, female/female



CE ACS EAC

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2"	3/4"



LL1529 | Built-in ball valve, full flow, female/female, flat lever handle



CE

Features		
Working pressure 25 bar (362.5 psi)		
Working temperature from -10°C to +120°C (from 14 °F to 248 °F)		
Thread ISO228 (equivalent to DIN 259 and BS2779)		
Opening/closing test 10000 times		
Size	1/2" 3/4" 1"	

LL1529-07 | Spindle extension for thermal insulation



Corresponding to valve item No. :						
LL1001	LL1003	LL1063	LL1095	LL1161	LL1162	LL1063B
LL1095B	LL1004	LL1067	LL1280	LL1136	LL1137	LL1138
LL1031	LL1071	LL1073				
Size	1/2" 3/4" 1"					