



GROOVED RESILIENT OS&Y GATE VALVE

UL/FM APPROVED

RED, MODEL: XZ81X

The Grooved Resilient OS&Y Gate Valve is designed for dependable flow control and isolation in fire protection and mechanical piping systems. Built with a ductile iron ASTM A536 body and grooved type connection, it delivers resilient-seated performance with long-lasting reliability. UL/FM approved and rated for maximum working pressure PN16, it is ideal for demanding fire protection and piping applications.


1. SPECIFICATIONS

Brand:	PINOLEAKPES
Product:	Grooved Resilient OS&Y Gate Valve
Model:	XZ81X
Body Material:	Ductile Iron ASTM A536
Connection:	Grooved Type
Approvals:	UL/FM
Finish / Color:	Red
Max. Working Pressure:	PN16
Application:	Fire Protection & Piping Systems

2. FEATURES & BENEFITS

-  Visible OS&Y position indication
-  Resilient seated shutoff performance
-  Ductile iron ASTM A536 construction
-  Grooved ends for faster installation
-  UL/FM approved for reliable service
-  Suitable for fire protection systems

3. PRODUCT OVERVIEW



4. APPLICATIONS

-  Fire protection lines
-  Sprinkler systems
-  Mechanical piping systems
-  Commercial and industrial facilities

5. STANDARDS / COMPLIANCE

-  **UL**
APPROVED
-  **FM**
APPROVED
-  **GROOVED
PIPING SYSTEM**
-  **INDUSTRIAL
QUALITY**

