



4" (100mm) DI A536 FIRELOCK END CAP

MODEL S006, GROOVED



The Victaulic® FireLock™ End Cap Model S006 is designed to close the end of a grooved piping system. Manufactured from ductile iron conforming to ASTM A536, it is engineered for use in fire protection systems, providing reliable performance, strength, and durability. Suitable for pressure ratings up to 300 psi (20.7 bar).



FIRE PROTECTION
APPROVED



HIGH PRESSURE
PERFORMANCE



STRONG &
DURABLE




RELIABLE
SEAL

FEATURES

- ✓ Designed for FireLock™ grooved systems
- ✓ Ductile iron construction ASTM A536
- ✓ Working pressure up to 300 psi (20.7 bar)
- ✓ UL / ULC Listed and FM Approved
- ✓ Corrosion resistant orange enamel finish
- ✓ Easy and fast installation
- ✓ Provides a leak-tight seal
- ✓ Ideal for fire protection applications

DIMENSIONS



SIZE	NOMINAL PIPE SIZE	A DIAMETER	B THICKNESS	WEIGHT
4"	100mm	4.72" (120mm)	0.87" (22mm)	2.20 lbs (1.00 kg)

* Dimensions are subject to change without prior notice.

SPECIFICATIONS

Brand	VICTAULIC
Product	FireLock™ End Cap
Model	S006
Size	4" (100mm)
Material	Ductile Iron ASTM A536
End Connection	Grooved
Working Pressure	300 psi (20.7 bar)
Finish	Orange Enamel
Approval	UL Listed / ULC Listed FM Approved
Application	Fire Protection Systems
Standards	ASTM A536, UL 213, ULC/ORD-C213 FM 1310

APPLICATIONS



FIRE SPRINKLER
SYSTEMS



FIRE PROTECTION
PIPING



COMMERCIAL
BUILDINGS



INDUSTRIAL
FACILITIES



WATER SUPPLY
SYSTEMS

**WHY CHOOSE
VICTAULIC FIRELOCK
END CAPS?**

- ✓ 100% Quality Tested
- ✓ High Strength & Durability
- ✓ Corrosion Resistant
- ✓ Easy Installation
- ✓ Leak-Proof Performance



www.pinoleakpes.com



nowserving@pinoleakpes.com



(02) 8285-7080



PI NOLEAK PES
ENTERPRISES CORPORATION

NO LEAK BETWEEN THE PIPES