

UNIVERSAL SLEEVE TYPE COUPLING


Product Feature:

- Ductile Iron GGG50 material with AKZO epoxy coated
- Working Pressure: PN16
- Equipped with Geomer 50 grade B bolts & nuts
- EPDM rubber seals
- Tolerance conforms to ISO 8062-3:2007 DCTG II-14
- Epoxy coating: mini 250 µm thickness
- Coating RAL 5017 FBE



Material Specifications:

Part No.	Part Name	Materials	Specifications:
1	Body	Ductile Iron	GGG50
2	End Ring	Ductile Iron	GGG50
3	Rubber Seal	Rubber	KRAIBURG RPDM
4	Bolt	Geomet 500 Grade B, Class 8.8	
5	Washer	Geomet 500 Grade B, Class 8.8	
6	Nut	Geomet 500 Grade B, Class 8.8	
7	Cap	Plastic	



Dimensions:

Size	Sealing Range	L	L1	L2	C	A	Bolts		Weight (kg)
							Dia x L	QTY	
50	58-74	200	100	80	76	172	M12 x 190	4	3.7
50/60/65	68-84	200	100	80	86	182	M12 x 190	4	3.7
80	84-105	200	102	75	107	211	M12 x 190	4	5.2
100	99-118	200	102	75	120	224	M12 x 190	4	5.4
100	109-133	210	100	75	135	242	M12 x 200	4	6.1
125	133-157	210	100	75	159	280	M12 x 200	4	7.1
150	157-182	230	118	85	185	296	M12 x 220	4	9.7
150	177-201	220	118	85	203	317	M12 x 210	4	9.7
200	194-215	230	118	85	217	322	M12 x 220	4	10.1
200	218-242	250	142	110	244	365	M12 x 240	4	13.3
250	242-268	250	142	110	270	390	M12 x 240	6	15.9
250	266-291	275	162	135	293	405	M12 x 265	6	16.8
250	280-305	275	162	125	307	425	M12 x 265	6	18.9
300	302-327	275	162	135	329	445	M12 x 265	6	20.4
300	324-350	290	160	125	352	475	M14 x 280	6	25.1
350	351-378	290	160	125	380	515	M14 x 280	6	29.5
350	386-410	290	162	130	412	550	M14 x 280	6	29.8
400	410-436	290	160	125	438	555	M14 x 280	6	30.9
400	436-462	275	160	120	464	585	M14 x 265	6	39.3