PI NOLEAK PES
ENTERPRISES CORPORATION
NO LEAK BETWEEN THE PIPES

QUYUAN®

FM APPROVED

4" DUCTILE IRON MECHANICAL ELBOW 45°

XGQT02 – 45° Elbow





Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimension L mm/in
25 1	33.7 1.315	300 2.07	44 1.732
32 1¼	42.4 1.66	300 2.07	45 1.772
40 1½	48.3 1.9	300 2.07	45 1.772
50 2	60.3 2.375	300 2.07	51 2.008
65 2½	73 2.875	300 2.07	57 2.244
65 30D	76.1 3	300 2.07	57 2.244
80 3	88.9 3.5	300 2.07	64 2.520
100 4	114.3 4.5	300 2.07	76 2.992
125 5½OD	139.7 5.5	300 2.07	83 3.268
150 6½ OD	165.1 6.5	300 2.07	89 3.504
150 6	168.3 6.625	300 2.07	89 3.504
200 8	219.1 8.625	300 2.07	108 4.252
250 10	273 10.75	300 2.07	121 4.764
300 12	323.9 12.75	300 2.07	133 5.236

RELIABLE PERFORMANCE | **STRONG & DURABLE** | **LEAK-TIGHT SEAL** | **EASY INSTALLATION**

FEATURES & BENEFITS

- 45° elbow for PVC to PVC piping systems
- Ductile iron construction for high strength
- Mechanical joint connection for secure sealing
- Orange epoxy coating for corrosion protection
- Suitable for potable water and general piping applications
- Meets industry standards for quality and performance

STANDARDS COMPLIANCE

AWWA C153	ISO 2531