

DI A536 FIRELOCK ELBOW 90° MODEL S001 GROOVED VICTAULIC

APPLICATIONS

- Fire protection piping systems
- Mechanical piping connections
- Water distribution lines
- Grooved system installations



Ductile Iron
ASTM A536



90° elbow fitting



Grooved ends



Durable red finish



For grooved
piping systems

SUITABLE FOR

WATER
SYSTEMS



FIRE PROTECTION
SYSTEMS



Note: For use only in applications compatible with Ductile Iron ASTM A536 and grooved systems.

TECHNICAL DATA

Product Type	FireLock Elbow 90°
Body Material	Ductile Iron ASTM A536
Model	S001
Connection	Grooved
Brand	Victaulic
Color	Red

FEATURES & BENEFITS

- ✓ Constructed from Ductile Iron ASTM A536 for strength and reliability
- ✓ Grooved ends ensure fast, secure, and leak-resistant connections
- ✓ Durable red finish provides corrosion resistance and easy identification
- ✓ Designed for grooved piping systems in fire and mechanical applications

DIMENSIONS & NOTES

NOMINAL SIZE DN (mm)	CONNECTION TYPE	ANGLE	DIMENSIONS (APPROX.) A x B (VARIABLE)	WEIGHT (APPROX.) VARIABLE	NOTES
25 – 300	Grooved	90°	Varies by size and model	Varies by size and model	Dimensions and weight vary by size/model. Refer to Victaulic catalogs or technical documentation for exact data.

NOTE: Dimensions are in millimeters unless otherwise specified. Weights are approximate.