



PINOLEAKPES

NO LEAK BETWEEN THE PIPES

PIPE CONNECTION SOLUTIONS
FOR A BETTER FLOW



S SCHMIDT

2" STAINLESS STEEL 316 BALL VALVE, THREADED, 2-PC DESIGN, 1000 WOG, FULL BORE



The SCHMIDT 2" Stainless Steel 316 Ball Valve is designed for reliable on/off flow control in a wide range of industrial applications. Built with a 2-piece body design, full bore for maximum flow, and NPT threaded ends for easy installation. Constructed from premium SS 316 for excellent corrosion resistance and long service life.



**CORROSION
RESISTANT**



**FULL
BORE**



**1000 WOG
RATING**



**DURABLE
& RELIABLE**



**EASY
INSTALLATION**



**2-PC
DESIGN**



**SUITABLE FOR
MULTIPLE APPLICATIONS**


FEATURES

- Investment cast body and cap
- Stainless Steel 316 for superior corrosion resistance
- Full bore design for unrestricted flow
- 2-piece design for easy maintenance
- Blow-out proof stem with locking device
- Adjustable stem packing
- NPT female threaded ends to ASME B1.20.1
- 100% leak tested

APPLICATIONS

- Water Supply Systems
- Chemical Processing
- Oil & Gas Industry
- HVAC Systems
- Food & Beverage Industry
- Marine & Offshore Applications

DIMENSIONS



SPECIFICATIONS

Brand	SCHMIDT
Size	2"
Material	Stainless Steel 316
Body Design	2-Piece
Connection	Threaded (NPT)
Port	Full Bore
Pressure Rating	1000 WOG
Temperature Range	-20°C to 200°C
Thread Standard	ASME B1.20.1 (NPT)
Seat	PTFE
Stem	Stainless Steel 316
Handle	Stainless Steel with Vinyl Grip
Application	Water, Oil, Gas, Air, Chemical Services
Country of Origin	China

DIMENSIONS (inch)

SIZE	d	L	H	W
2"	2.00	4.72	3.34	8.66

Note: Dimensions are approximate and may vary slightly.
All dimensions are in inches.



(02) 8 362 8888

sales@pinoleakpes.com

www.pinoleakpes.com

**QUALITY PRODUCTS.
TRUSTED SOLUTIONS.**

DISTRIBUTED BY: